

INSTRUCTIONS FOR USE

ALL-YEAR PVC GAZEBO ROOF

Manufacturer: Shade4you sp. z o.o.
 1 Szczawnicka Street,
 60-471 Poznań, Poland
office@shade4you.eu | www.shade4you.eu



Figure 1: Sailing roof

- The roof should be installed horizontally, at a slant (approximately 8 per cent) to drain any water that might collect on it during rainfall. It serves to shade and decorate the designated area, it also has rainproof properties and should be used for its intended purpose.
- After the season, the roof can be dismantled, cleaned, dried and stored in a dry place, preferably in the form of a rolled so that there are no creases in the fabric.
- The roof is made of very strong 650 g/m² tarpaulin material as an option can have a 0.7 mm transparent window. The standard finish is eyeleting all round (overlapping - Fig. 1), allowing the structure to be covered.
- The roof is sold with locks and screws for self-assembly on the pre-prepared constructions.
- The structure should be robust to support the roof and the loads that will be placed on it in the event of inclement weather.
- The material is allowed to discolour up to 8% per year.
- The roof is not a maintenance-free product. It must not be exposed to high winds, snow and/or hail deposits and/or rain. As the roof may be used all year round, snow/hail should be removed from the roof to avoid damaging the structure or the roof should be dismantled if it is not possible to respond on an ongoing basis. A dirty roof should be cleaned. Dirt should be regularly removed from the fabric with a soft brush and, if necessary, washed with a sponge solution of neutral ph soap and water at a maximum temperature of 30° C, followed by a rinse with water.
- The roof must be inspected regularly for damage. A damaged roof must be taken out of service until it is repaired.
- The roof should be installed in a location that allows it to dry completely or be dried during operation.
- The roof, should be carefully hung in the place for which it was sewn to provide as flat a surface as possible, as shown in the instructional video <https://www.youtube.com/watch?v=UupMA3pcCBw&t=4s>.
- The installation of the roof is recommended to be carried out by a minimum of two people.



Figure 2: Installation of the Roman blind



READ THE QR CODE and WATCH
THE INSTRUCTIONAL FILM ON
YOUTUBE



INSTRUCTIONS FOR USE
ALL-YEAR PVC GAZEBO ROOF

MOUNTING PROPOSAL:

1. spread the roof flat where it is to be hung;
2. place/support the roof on the structure to which it is to be fitted;
3. try the roof on to determine the installation of the edge, corner meshes - centre the roof;
4. screw the outermost brackets (where the roof meshes will fall) onto the structure and mount them on the them the roof;
5. Carefully screw on the handles one at a time, starting from the right or left side and fasten the eyelet lock at once;
6. in the event of wrinkling of the fabric - move the previously installed handle in the wrong place.

Standard finish

**WHEN PURCHASING A PVC PATIO ROOF, YOU RECEIVE THE FOLLOWING BRACKETS IN QUANTITY
ADAPTED TO THE MESH IN THE TERRACE ROOF**



Haven't found the right kit? Looking
for a fix for masonry, metal or
other?

Ask your advisor!



FAST CONTACT tel: +48 518 537 385